

"Express Mail" mailing label number EL486651283US
Date of Deposit December 19, 2000

Atty Docket No. 00P7662US01

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

This is a U.S. Patent Application for:

**TITLE: SYSTEM AND METHOD FOR ANALYZING AND GENERATING
 SUPPLEMENTARY SERVICE DATA UNITS IN PACKET BASED
 MULTIMEDIA COMMUNICATIONS SYSTEMS**

Inventor #1: Florian Trinkwalder
Address: 534 Giuffrida Avenue, #A, San Jose, California 95123
Citizenship: Germany

Inventor #2: Mark E. Clark
Address: 2986 Little Rock Drive, San Jose, California 95133
Citizenship: USA

Inventor #3: Mark Skrzynski
Address: 1800 42nd Avenue, Capitola, California 95010
Citizenship: USA

**SYSTEM AND METHOD FOR ANALYZING AND GENERATING
SUPPLEMENTARY SERVICE DATA UNITS IN PACKET BASED
MULTIMEDIA COMMUNICATIONS SYSTEMS**

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of commonly owned U.S. Patent Application Serial No. 09/586,408, filed June 1, 2000, and titled "System and Method for Sending Messages Defined by an ASN.1 Structure from an Application to the Signaling Entity and Vice Versa Via a Tree Structured Text String," which is hereby incorporated by reference in its entirety as if fully set forth herein.

RESERVATION OF COPYRIGHT

A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the U.S. Patent and Trademark Office patent file or records available to the public, but otherwise reserves all copyright rights whatsoever.

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

The present invention relates to telecommunication systems and, particularly, to a system and method for sending messages from an application to signaling entities and, for particular embodiments, the sending of APDUs between H.323/H.450 endpoints.

DESCRIPTION OF THE RELATED ART

The Abstract Syntax Notation One (ASN.1), described in the International Telecommunications Union (ITU) X.680 and X.691 specifications, defines a data structure protocol for describing messages to be exchanged between distributed computer systems. ASN.1 defines data units independently of system architecture. Because of this, ASN.1 is used to generate programming language code that forms the core of a wide variety of

messaging systems applications, including ITU-T Recommendation H.323.

The ITU-T Recommendation H.323 is a group of specifications defining the operation of a multimedia communication system over packet networks.

- 5 The ITU-T Recommendation H.323 specifies H.245 control signaling for negotiation of media channel usage, Q.931 (H.225.0) for call signaling and call setup, H.225.0 Registration, Admission, and Status (RAS), H.450 for supplementary services, and RTP/RTCP for sequencing audio and video packets. An exemplary system implementing the Recommendation H.323 is the HiPath™ 5500 system, available from Siemens Information and
- 10 Communication Networks, Inc.

H.323-based systems use ASN.1 coded messages and protocol state machines for describing the application protocol data units (APDU) or packets of data used for signaling between H.323 endpoints, servers, gateways, and gatekeepers.

- 15 The processing of H.323 ASN.1 messages is typically implemented in a protocol stack, and its functions are accessed by application programs through application programming interfaces (API). The software primitives of the APIs are typically written with programming languages, such as C, C++, and Java, and all the associated parameters are expressed and declared in
- 20 the corresponding language.

- Whenever new features, such as new parameters or completely new supplementary services are added to the protocol stack of a software product, such as an H.323 application, software changes must be done in three layers:
- 25 new functional entities must be added to the protocol stack; new parameters or programming primitives must be added to the API; and applications and their user interfaces must be changed or enhanced to allow user access to the new features. Each operation carried out by the new feature must be callable via an API that must be explicitly exported to the application. The changes must be made at the source code level, and the new software
- 30 system must be recompiled and linked together and loaded to the customer's target system.

Thus, changes and additions to the software require replacement of

the software in the target system. While software can be downloaded remotely, an interruption of the target system's operation occurs, which can hinder the simple "plugging in" of new features to the system.

Moreover, unless the API is modified, the application cannot access
5 new features. Thus, even relatively small changes and additions to the signaling protocols and related protocol stacks require relatively high development effort, since the API source code must be modified.

Therefore, there is a need for an improved method for updating the protocol stack of an API based software product. There is particularly a need
10 for an improved method for updating the processing of ASN.1 messages in an H.323 telecommunications system.

Further, as is known, H.225 messages are used for call signaling to establish a connection between endpoints. Initially, an H.225.0 RAS (registration, admission, status) channel is established between an endpoint
15 and a gatekeeper (in the gatekeeper-routed call model). After the RAS signaling channel is established, an H.225.0 call signaling channel is established between endpoints. H.225.0 call signaling messages include SETUP, ALERTING, CONNECT, RELEASE COMPLETE, and FACILITY. The user-user information element of an H.225 message can carry an H.450
20 APDU (application protocol data unit) for H.450 supplementary services. Such services are call-related services beyond the basic call and can include Call Forwarding, Call Transfer, Call Waiting, Message Waiting Indication, Conference, and the like.

As can be appreciated, newly implemented H.450 supplementary
25 service features must be tested with all possible normal and exceptional events. To perform these tests, various H.450 messages must be sent and received by the endpoints. As such, there is a need for a system and method for sending, receiving, and displaying such test messages.

30 SUMMARY OF THE INVENTION

These and other problems in the prior art are overcome in large part by a system and method according to the present invention. According to the

present invention, signaling messages and parameters that are defined by an ASN.1 structure are sent as a tree-structured text string from an application to a signaling entity (SE) and vice versa. As new signaling entities are added to support new features, the features can receive and send primitives without
5 the programmer having to change or expand the API.

According to an implementation of the present invention, application programming interfaces (APIs) are provided which implement a first recursive function for interpreting text strings representative of ASN.1 structures for communicating with an application program. A second recursive function
10 receives and interprets ASN.1 value trees from signaling entities (SE).

According to an implementation of the invention, an H.450 test client is provided. The H.450 test client can send and receive H.450 application protocol data units in any H.225 message. The test client allows for the setting of desired H.450 parameters and allows for the display of the H.450
15 message itself.

BRIEF DESCRIPTION OF THE DRAWINGS

A better understanding of the invention is obtained when the following detailed description is considered in conjunction with the following drawings in
20 which:

FIG. 1 is a block diagram illustrating an implementation of the present invention;

FIG. 2 is a functional diagram illustrating an implementation of the present invention;

25 FIG. 3 is a flowchart illustrating an implementation of the present invention;

FIG. 4 is a functional diagram of an implementation of the present invention;

FIG. 5 is a flowchart illustrating operation of an implementation of the
30 invention;

FIG. 6 is a graphical user interface according to an implementation of the present invention;

FIG. 7 is a diagram of another aspect of the graphical user interface of FIG. 6;

FIG. 8 is an exemplary H.225 packet;

FIG. 9 and FIG. 10 are exemplary graphical user interfaces according to an implementation of the invention;

FIG. 11 is a flowchart illustrating operation of an implementation of the invention;

FIG. 12A and FIG. 12B are exemplary graphical user interfaces according to an implementation of the invention;

FIG. 13 is an exemplary graphical user interface according to an implementation of the invention; and

FIG. 14 is a diagram of a graphical user interface according to an implementation of the invention.

DETAILED DESCRIPTION OF THE INVENTION

FIGs. 1- 14 illustrate an improved system and method according to the present invention. A first implementation is a system and method for configuring a communication system with system updates without having to recompile associated application programming interfaces. In a second implementation, an H.450 test client is provided. The H.450 test client can send and receive H.450 application protocol data units in any H.225 message. The test client allows for the setting of desired H.450 parameters and allows for the display of the H.450 message itself.

ASN.1 Text Strings

An exemplary computer system implementing a communication system according to an implementation of the invention is shown in FIG. 1. As will be described in greater detail below, the system 102 may be embodied as an H.323 terminal. In particular, the system may be embodied as a personal computer, such as an x86 compatible personal computer or an Apple Macintosh G4. The computer 102 includes a processor 11 adapted to implement computer code according to the present invention. Further,

according to an implementation of the present invention, the processor 11 implements an operating system (not shown) for generating a graphical user interface (GUI) 520 to control system operation.

As shown in FIG. 1, an application program 502, such as a telephony application, one or more APIs 506, and one or more signaling entities 510a-510n are resident. As will be explained in greater detail below, the APIs 506 implement recursion functions 508 that allow ASN.1 text strings to be passed to the application 502 and the signaling entities 510. Thus, as will be explained in greater detail below, when upgrading the system, i.e., when new signaling entities are provided, the APIs need not be altered.

More particularly, FIG. 2 is a functional diagram of the system according to the present invention. The system includes an application program 502, such as a telephony program. The application program 502 communicates via text strings 503a, b with one or more APIs 506, as will be explained in greater detail below. The text strings 503a,b contain the ASN.1 tree structure of the message and the corresponding values.

The ASN.1 tree structure is defined in terms of "valuetrees" and "syntaxtrees." The syntaxtree is static and contains the syntax of all possible information elements of a message structure. The valuetree is dynamic and contains all information elements that exist for a specific message. The value tree also contains the values of the various fields.

In one implementation, the structure of the message, i.e., the syntaxtree is provided to the application program 502 ahead of time. In that case, although the application 502 and the corresponding signaling entity 510 must be updated in order to add new features, the API 506 remains the same.

In an alternate implementation, the structure and syntax of the message are provided to the application program 502 from the stack (not shown). In that case, the application program 502 will first call the corresponding API to retrieve the syntaxtree structure for the message from the stack. In this case, to add new features, both the application program 502 and the API 506 could be left unchanged. The only change then required to

the system is new signaling entity script.

In operation, a first recursive function 508a receives the syntactree text strings 503a, fills in the valuetrees, and passes them to one or more signaling entities 510. The signaling entities may be any entities adapted to generate
 5 encodeable data according to specified functions. In particular, the signaling entities 510 may be embodied as H.450 signaling entities. Such signaling entities include the Message Waiting Indication (MWI), Call Transfer, Call Diversion, Call Hold, Call Waiting Call Completion, Call Pickup, and Number Identification signaling entities. The signaling entities 510 may be
 10 implemented in protocol description language (PDL) scripts. Further details on PDL scripts are available from Radvision, Ltd. The PDL scripts contain the state machine code of the signaling entities and also implement machines arranged in a tree structure.

In turn, the signaling entities 510 communicate their respective
 15 APDUs (application protocol data unit) for ASN.1 encoding/decoding 512. The ASN.1 encoded octet strings are then provided onto the network 514.

When messages are received from the network, the ASN.1 octet strings are decoded, and the corresponding APDUs are provided to the appropriate signaling entities 510. The APIs 506 then receive the message
 20 values from the signaling entities 510, interpret them using a second recursion function 508b, and pass them as text strings to the application.

Operation of an embodiment of the invention is illustrated with reference to the flowchart of FIG. 3. In a step 452, an application program 502 builds up a tree-structured text string, i.e., the valuetree, for a message,
 25 such as an H.450 message. In a step 454, the API 506 receives the valuetree string and fills the information elements into the valuetree. In a step 456, the appropriate signaling entity 510 is created according to the operation in the message. In a step 458, the signaling entity sends the message in an H.450 APDU over the network. In a step 460, the H.450 APDU is received
 30 from the network by the receiving party at its corresponding remote signaling entity. In a step 462, the remote signaling entity sends the message's valuetree to its API. In a step 464, the API reads out the valuetree and sends

the information elements to the application program in a tree-structured text string. Finally, in a step 466, the application program receives the tree-structured text string and processes the information elements.

Operation of a particular implementation of the present invention may be illustrated by way of a specific example. According to a specific embodiment, code implementing the example follows as an Appendix. Shown in FIG. 4 is a software model of the example. The model includes an MWI Test Utility 502a, i.e., Application Program. The Message Waiting Test utility 502a tests the H.450 message waiting indication supplementary service. The Message Waiting supplementary service indicates on the served user that messages are waiting on the message center.

The model also includes an H.450 Test API 506a, a Message Center Signaling Entity 510a, a Served User Signaling Entity 510c, and a Message Linker 510b. To signal the relevant information over the network, APDUs with activation, deactivation, and interrogation operations are sent to and received from the network by the Served User Signaling Entity 510c and the Message Center Signaling Entity 510a.

The Message Linker 510b functions to provide a distribution process by determining to which signaling entity a specific text primitive or APDU is to be sent. That is, messages are sent to and received from the signaling entities 510a via the Message Linker 510b.

As seen in the Appendix, the H450 Test API 506a employs the files H450api.c, H450api.h, and H450struct.h. The Supplementary Service employs the files MWI.pdf and MWI-operations.asn. The H450 Test API
25 implements initAPI, setCallback, initH450Root, and endH450Root initialization and termination functions. The initAPI function initializes the API. The setCallback function sets the callback. The initH450Root creates and initializes, and the end450Root function terminates, the H450 root protocol.

As is known, when a PDL state machine is executed, the resulting data
30 structure is called a “process.” As the PDL engine executes the state
machines, the processes are also arranged in a tree structure and the
process tree is built in a hierarchical manner. When a process activates

another process, the new process is located under the existing process in the process tree, the new process being defined as a "child" process of the existing process.

In addition to the process tree, the PDL engine builds another tree called the "protocol" tree. A protocol is a data structure that allows interaction between the application and the PDL machines. The protocol tree has a similar structure to that of the process tree, but not all of the elements of the process tree are recreated in the protocol tree.

The Test H450 API 506a (FIG. 4) implements createH450protocol, closeH450protocol, newH450RootChild, and newH450Child protocol functions. The createH450protocol function creates a new H450 protocol under the protocol root. The closeH450protocol closes the H450 protocol. The newH450RootChild is called when a new protocol is created under the protocol root. The newH450Child function is called when a new child is created under the message linker protocol.

The H450 test API 506a implements the following message functions: sendmessage450, newH450message, fillin, and recursion. The sendmessage450 function is called when a new message is sent from the application to the H450 protocol. The newH450message is called if the applsend function is executed in the PDL script in order to send a message back to the application.

The fillin() and recursion() function to transform the tree-structured text-strings into valuetree structures and vice versa. The fillin() function receives the string as a parameter and fills in the various fields in the valuetree (XMLstring -> valuetree). The recursion() function reads out the valuetree and parses its nodes and values into a textstring (valuetree -> XMLstring).

FIG. 5 is a flowchart illustrating operation of the embodiment of the invention. In a step 650, the application program builds up a tree-structured text string for an H.450 message. In a step 652, the API receives the text string and fills in the information elements into the value tree using the fillin() function and creates the Message Linker protocol, i.e., the root protocol. In a

step 654, the Message Linker creates the Signaling Entity according to the operation in the message. In a step 656, the Signaling Entity sends the message in an H.450 APDU over the network. In a step 658, the Message Linker receives the H.450 APDU from the network and creates the Signaling Entity according to the operation received. In a step 660, the Signaling Entity receives the APDU from the Message Center and sends its value tree to the API. In a step 662, the API reads the valuetree using the recursion() function and sends the information elements to the application in a tree-structured text string. Finally, in a step 664, the application receives the tree-structured text string and processes the information elements.

As noted above, one aspect of implementing the invention is a graphical user interface. FIG. 6 illustrates an exemplary graphical user interface 520 for the message waiting indication (MWI) test utility. As shown, the graphical user interface 520 includes a message center (MC) test control 524 and a served user test control 526. The GUI 520 further includes a text display region 522, used to display the ASN.1 text strings. The message center test control 524 includes an Activate Request button 528, a Deactivate Request button 530, an Interrogation Response (ack) button 532, and an Interrogation Response (rej) button 534. The served user test control 526 includes an Activate Response (ack) button 536, an Activate Response (rej) button 538, a Deactivate Response (ack) button 540, a Deactivate Response (rej) button 542, and an Interrogation Request button 544. The Message Waiting Indication (MWI) service activates an indication device (e.g. LED) on the served user endpoint if a message (e.g., voicemail) is waiting on the message center. Three operations can be sent over the network: Activation (to activate the MWI (turn on LED)); Deactivation (to deactivate the MWI (turn off LED)); Interrogation (the served user queries its MWI status).

The "XXX Request Buttons" (where XXX stands, e.g., for Activation) request to send the corresponding operation in an H.450 APDU to the peer entity. If the peer entity receives an indication of an operation (e.g. activation), it will respond by either acknowledging the request by pressing

the "XXX Response (ack) Button" or by rejecting the request by pressing the "XXX Response (rej) Button".

In operation, a user can push a button, such as Activate Request 528.

In response, a dialog window 600 (FIG. 7) is displayed. As shown, the dialog window 600 includes a plurality of data fields, and a SAVE button and a
 5 SEND button. Shown are servedUserNr, basicService, msgCenterId, nbOfMessages, originatingNr, timestamp, and priority fields. Once filled in, by pressing the SAVE button, the values are stored in a h4507.ini file; by pressing SEND, the message is sent as a text string to the signaling entity.

10

H.450 Test Utility

As noted above, one aspect of the invention is an ability to send and receive any H.450 protocol data unit (PDU) in any H.225 message. More particularly, FIG. 8 illustrates an exemplary H.225 signaling message 800. As
 15 shown, the signaling message 800 includes a TCP header 802 and an H.225.0 V2 message 804. The H.225.0 V2 message 804 is representative of, for example, a SETUP, CONNECT, FACILITY, etc., message. The H.225.0 V2 message 804 includes H.225.0V2/Q.931 information elements 806, setup information element 808 and an H.450 PDU 810. The H.450 PDU 810
 20 includes a network facility extension (NFE) 812, an interpreter APDU (IAPDU) 814, an H.450 feature 816, an MSI extension 818, and an MSI specific feature 820. The NFE 812 defines the type of source and destination of the operation. The IAPDU 814 defines what the receiver is to do if it does not understand the command. The H.450 feature 816 is the APDU itself, and
 25 contains an MSI extension which identifies the manufacturer, as does the MSI specific feature 820.

As will be explained in greater detail below, the present invention allows the user to send test H.225 messages, with or without H.450 APDUs. If an H.450 APDU is to be sent, the user can select the specific H.450 APDU
 30 and any combination of information elements and network facility extension. The messages are then sent and received, as will be discussed in greater detail below.

A graphical user interface is used to build the H.450 APDU. A graphical user interface in accordance with an implementation of the present invention is shown in FIG. 9. The GUI 900 allows the user to select the H.225 message which is to be tested. For example, the user can select SETUP
 5 904a, ALERTING 904b, or FACILITY 904c buttons to select the corresponding H.225 message. One or more informational fields 902, such as called party and calling party phone number and alias may also be provided. Further, a list field 906 is provided to display the received H.450 message in an XML-like syntax, as generally described above. The list field
 10 906 displays the H.225 message in which the H.450 APDU was received, and also displays all the H.450.1 information elements.

If the user decides to send an H.225 message, e.g., by clicking on SETUP, and after inputting the target number or name, the dialog box 950 of FIG. 10 is displayed. The dialog box 950 allows setting the H.450 information
 15 elements. Thus, the dialog box 950 includes an interpretation APDU select dialog 952 and a network facility extension select dialog 954. Using the pulldown 953, the user can select any of a plurality of interpretation APDUs. Alternatively, by deactivating the checkbox 951 the user can elect to send an H.225 message without the IAPDU. Similarly, the user can elect to send no
 20 network facility extension, by clicking on the checkbox 955.

The user can input a source and destination entity using the source entity dialog box 956 and destination entity dialog box 958, respectively. The source entity dialog allows the user to enter an entity type 960a and a source entity address 962. The source entity address 962 allows a user to input a
 25 value and address type 966a, 968a. As shown, a Party Number type has been selected. The party number dialog 970a allows the user to select a type of party number 972a and then, more specifically, the type of private 974a or public 976a party number. Alternatively, a transport address 978a may be supplied.

30 Similarly, the destination entity dialog can be used to select an entity type 960b, and includes a destination entity address dialog 964. The destination entity address dialog can be used to input a value 966b and select

a destination entity address type 968b. As shown, a transported type has been selected. The transport ID, e.g., IP address and port, may be input using the dialog 978b. If a party number type had been selected, the user could input a party number type 972b and a private party number type 974b or public party number type 976b.

The entries may be saved by clicking on SAVE 980. Alternatively, the H.225 message may be sent without the H.450 APDU by clicking on button 982 or with the APDU by clicking on button 984.

FIG. 12A and FIG. 12B illustrate graphical user interfaces according to another implementation of the invention. FIG. 12A illustrates a Select H450 APDU Dialog 1200. The Dialog 1200 appears, for example, when Setup (FIG. 9) is clicked. The Select H450 APDU Dialog includes OK button 1202, Cancel button 1204, and New button 1206, as well as List dialog 1208. By clicking on the Cancel button 1204, the user can decide not to send an APDU with this H.225 message, in which case, the Dialog 1200 will close and the message will be sent immediately. Clicking the New button 1206 will start an H450 Builder Application, as will be explained in greater detail below, which allows the building of a new H450 APDU and adding it to the List dialog 1208. After the APDU is created and saved and the user closes the APDU Builder application, the List dialog 1208 is refreshed to show the new APDU.

If the user highlights an APDU in the List dialog 1208 and clicks the OK button 1202, the Select Operation Argument Dialog 1210 (FIG. 12B) appears. The Select Operation Argument Dialog 1210 includes an OK button 1212, a Cancel button 1214, a New button 1216, and a List Dialog 1218.

By clicking the Cancel button 1214, the user can decide not to send an Argument with this APDU, which will close the dialog and send the message immediately. Clicking on New 1216 will start the H450 Builder Application which allows the user to build a new argument and add it to the List dialog 1218. Once the new Argument is created and the Builder is exited, the List 1218 is refreshed.

If the user highlights an Argument in the List 1218 and clicks the OK button 1212, the H.450 Client processes all necessary RAS procedures and

send the setup message together with the H.450 APDU to the specified destination.

Operation of the H450 Builder is shown in greater detail with reference to FIG. 13 and FIG. 14. More particularly, FIG. 13 illustrates a Create APDU dialog 1300. The Create APDU dialog 1300 includes an OK button 1302, a Cancel button 1304 and an entry dialog 1306. If the user presses Cancel 1304, the application terminates.

Otherwise, at startup, the Builder first asks what type of APDU the user wants to create. The user does so by typing in the appropriate APDU in the Entry dialog 1306. The user can type in "h4501" to build an H.450 APDU or "h450x" to build an argument, where x refers to the number of the H.450 recommendation. When the user clicks "OK" 1302, the Builder GUI (FIG. 14) appears.

The APDU Builder 1400 displays a tree control, which displays the whole syntaxtree of the H450 APDU. By clicking on the nodes of the tree, the user can select or deselect nodes for building. If a leaf node (i.e., an end node) is selected, a dialog box (not shown) appears for the user to fill in data.

For example, FIG. 14 illustrates a syntaxtree for an H4501 supplementary service. The user can select network facility extension, InterpretationAPDU, and serviceAPDU nodes. If the user selects networkfacilityextension, the user can choose a SourceEntity, a SourceEntityAddress, and a DestinationEntity and DestinationEntityAddress. If the user selects destinationEntityAddress, a variety of choices are available, such as H323-ID, url-ID, and the like. The user can select one and fill in the appropriate value.

Turning now to FIG. 11, a flowchart illustrating operation of an implementation of the invention is shown. In step 1000, the user uses GUI 900 (FIG. 9) to select a particular H.225 message for sending. In a step 1002, a selection of the IAPDU may be made, using the checkbox 951 and the dialog 953 (FIG. 10) or the Select APDU, Select Operation Argument dialogs (FIG. 12A-12B). In a step 1004, a selection of the Network Facility Extension may be made using the checkbox 935 and the dialog 954 or the

Builder 1400. As discussed above, this can include selection of a variety of source and destination entities, and addresses, including party numbers or transport IDs. In a step 1006, the user can elect to save the filled in information or send the H.225 message with or without the APDU, using
 5 buttons 980, 984, or 984 (or the dialogs 1200, 1210, 1300, 1400). In a step 1005, the H.450 IAPDU is displayed.

The invention described in the above detailed description is not intended to be limited to the specific form set forth herein, but is intended to cover such alternatives, modifications and equivalents as can reasonably be
 10 included within the spirit and scope of the appended claims.

FIG. 14
 FIG. 15
 FIG. 16
 FIG. 17
 FIG. 18
 FIG. 19
 FIG. 20
 FIG. 21
 FIG. 22
 FIG. 23
 FIG. 24
 FIG. 25
 FIG. 26
 FIG. 27
 FIG. 28
 FIG. 29
 FIG. 30
 FIG. 31
 FIG. 32
 FIG. 33
 FIG. 34
 FIG. 35
 FIG. 36
 FIG. 37
 FIG. 38
 FIG. 39
 FIG. 40
 FIG. 41
 FIG. 42
 FIG. 43
 FIG. 44
 FIG. 45
 FIG. 46
 FIG. 47
 FIG. 48
 FIG. 49
 FIG. 50
 FIG. 51
 FIG. 52
 FIG. 53
 FIG. 54
 FIG. 55
 FIG. 56
 FIG. 57
 FIG. 58
 FIG. 59
 FIG. 60
 FIG. 61
 FIG. 62
 FIG. 63
 FIG. 64
 FIG. 65
 FIG. 66
 FIG. 67
 FIG. 68
 FIG. 69
 FIG. 70
 FIG. 71
 FIG. 72
 FIG. 73
 FIG. 74
 FIG. 75
 FIG. 76
 FIG. 77
 FIG. 78
 FIG. 79
 FIG. 80
 FIG. 81
 FIG. 82
 FIG. 83
 FIG. 84
 FIG. 85
 FIG. 86
 FIG. 87
 FIG. 88
 FIG. 89
 FIG. 90
 FIG. 91
 FIG. 92
 FIG. 93
 FIG. 94
 FIG. 95
 FIG. 96
 FIG. 97
 FIG. 98
 FIG. 99
 FIG. 100
 FIG. 101
 FIG. 102
 FIG. 103
 FIG. 104
 FIG. 105
 FIG. 106
 FIG. 107
 FIG. 108
 FIG. 109
 FIG. 110
 FIG. 111
 FIG. 112
 FIG. 113
 FIG. 114
 FIG. 115
 FIG. 116
 FIG. 117
 FIG. 118
 FIG. 119
 FIG. 120
 FIG. 121
 FIG. 122
 FIG. 123
 FIG. 124
 FIG. 125
 FIG. 126
 FIG. 127
 FIG. 128
 FIG. 129
 FIG. 130
 FIG. 131
 FIG. 132
 FIG. 133
 FIG. 134
 FIG. 135
 FIG. 136
 FIG. 137
 FIG. 138
 FIG. 139
 FIG. 140
 FIG. 141
 FIG. 142
 FIG. 143
 FIG. 144
 FIG. 145
 FIG. 146
 FIG. 147
 FIG. 148
 FIG. 149
 FIG. 150
 FIG. 151
 FIG. 152
 FIG. 153
 FIG. 154
 FIG. 155
 FIG. 156
 FIG. 157
 FIG. 158
 FIG. 159
 FIG. 160
 FIG. 161
 FIG. 162
 FIG. 163
 FIG. 164
 FIG. 165
 FIG. 166
 FIG. 167
 FIG. 168
 FIG. 169
 FIG. 170
 FIG. 171
 FIG. 172
 FIG. 173
 FIG. 174
 FIG. 175
 FIG. 176
 FIG. 177
 FIG. 178
 FIG. 179
 FIG. 180
 FIG. 181
 FIG. 182
 FIG. 183
 FIG. 184
 FIG. 185
 FIG. 186
 FIG. 187
 FIG. 188
 FIG. 189
 FIG. 190
 FIG. 191
 FIG. 192
 FIG. 193
 FIG. 194
 FIG. 195
 FIG. 196
 FIG. 197
 FIG. 198
 FIG. 199
 FIG. 200
 FIG. 201
 FIG. 202
 FIG. 203
 FIG. 204
 FIG. 205
 FIG. 206
 FIG. 207
 FIG. 208
 FIG. 209
 FIG. 210
 FIG. 211
 FIG. 212
 FIG. 213
 FIG. 214
 FIG. 215
 FIG. 216
 FIG. 217
 FIG. 218
 FIG. 219
 FIG. 220
 FIG. 221
 FIG. 222
 FIG. 223
 FIG. 224
 FIG. 225
 FIG. 226
 FIG. 227
 FIG. 228
 FIG. 229
 FIG. 230
 FIG. 231
 FIG. 232
 FIG. 233
 FIG. 234
 FIG. 235
 FIG. 236
 FIG. 237
 FIG. 238
 FIG. 239
 FIG. 240
 FIG. 241
 FIG. 242
 FIG. 243
 FIG. 244
 FIG. 245
 FIG. 246
 FIG. 247
 FIG. 248
 FIG. 249
 FIG. 250
 FIG. 251
 FIG. 252
 FIG. 253
 FIG. 254
 FIG. 255
 FIG. 256
 FIG. 257
 FIG. 258
 FIG. 259
 FIG. 260
 FIG. 261
 FIG. 262
 FIG. 263
 FIG. 264
 FIG. 265
 FIG. 266
 FIG. 267
 FIG. 268
 FIG. 269
 FIG. 270
 FIG. 271
 FIG. 272
 FIG. 273
 FIG. 274
 FIG. 275
 FIG. 276
 FIG. 277
 FIG. 278
 FIG. 279
 FIG. 280
 FIG. 281
 FIG. 282
 FIG. 283
 FIG. 284
 FIG. 285
 FIG. 286
 FIG. 287
 FIG. 288
 FIG. 289
 FIG. 290
 FIG. 291
 FIG. 292
 FIG. 293
 FIG. 294
 FIG. 295
 FIG. 296
 FIG. 297
 FIG. 298
 FIG. 299
 FIG. 300
 FIG. 301
 FIG. 302
 FIG. 303
 FIG. 304
 FIG. 305
 FIG. 306
 FIG. 307
 FIG. 308
 FIG. 309
 FIG. 310
 FIG. 311
 FIG. 312
 FIG. 313
 FIG. 314
 FIG. 315
 FIG. 316
 FIG. 317
 FIG. 318
 FIG. 319
 FIG. 320
 FIG. 321
 FIG. 322
 FIG. 323
 FIG. 324
 FIG. 325
 FIG. 326
 FIG. 327
 FIG. 328
 FIG. 329
 FIG. 330
 FIG. 331
 FIG. 332
 FIG. 333
 FIG. 334
 FIG. 335
 FIG. 336
 FIG. 337
 FIG. 338
 FIG. 339
 FIG. 340
 FIG. 341
 FIG. 342
 FIG. 343
 FIG. 344
 FIG. 345
 FIG. 346
 FIG. 347
 FIG. 348
 FIG. 349
 FIG. 350
 FIG. 351
 FIG. 352
 FIG. 353
 FIG. 354
 FIG. 355
 FIG. 356
 FIG. 357
 FIG. 358
 FIG. 359
 FIG. 360
 FIG. 361
 FIG. 362
 FIG. 363
 FIG. 364
 FIG. 365
 FIG. 366
 FIG. 367
 FIG. 368
 FIG. 369
 FIG. 370
 FIG. 371
 FIG. 372
 FIG. 373
 FIG. 374
 FIG. 375
 FIG. 376
 FIG. 377
 FIG. 378
 FIG. 379
 FIG. 380
 FIG. 381
 FIG. 382
 FIG. 383
 FIG. 384
 FIG. 385
 FIG. 386
 FIG. 387
 FIG. 388
 FIG. 389
 FIG. 390
 FIG. 391
 FIG. 392
 FIG. 393
 FIG. 394
 FIG. 395
 FIG. 396
 FIG. 397
 FIG. 398
 FIG. 399
 FIG. 400
 FIG. 401
 FIG. 402
 FIG. 403
 FIG. 404
 FIG. 405
 FIG. 406
 FIG. 407
 FIG. 408
 FIG. 409
 FIG. 410
 FIG. 411
 FIG. 412
 FIG. 413
 FIG. 414
 FIG. 415
 FIG. 416
 FIG. 417
 FIG. 418
 FIG. 419
 FIG. 420
 FIG. 421
 FIG. 422
 FIG. 423
 FIG. 424
 FIG. 425
 FIG. 426
 FIG. 427
 FIG. 428
 FIG. 429
 FIG. 430
 FIG. 431
 FIG. 432
 FIG. 433
 FIG. 434
 FIG. 435
 FIG. 436
 FIG. 437
 FIG. 438
 FIG. 439
 FIG. 440
 FIG. 441
 FIG. 442
 FIG. 443
 FIG. 444
 FIG. 445
 FIG. 446
 FIG. 447
 FIG. 448
 FIG. 449
 FIG. 450
 FIG. 451
 FIG. 452
 FIG. 453
 FIG. 454
 FIG. 455
 FIG. 456
 FIG. 457
 FIG. 458
 FIG. 459
 FIG. 460
 FIG. 461
 FIG. 462
 FIG. 463
 FIG. 464
 FIG. 465
 FIG. 466
 FIG. 467
 FIG. 468
 FIG. 469
 FIG. 470
 FIG. 471
 FIG. 472
 FIG. 473
 FIG. 474
 FIG. 475
 FIG. 476
 FIG. 477
 FIG. 478
 FIG. 479
 FIG. 480
 FIG. 481
 FIG. 482
 FIG. 483
 FIG. 484
 FIG. 485
 FIG. 486
 FIG. 487
 FIG. 488
 FIG. 489
 FIG. 490
 FIG. 491
 FIG. 492
 FIG. 493
 FIG. 494
 FIG. 495
 FIG. 496
 FIG. 497
 FIG. 498
 FIG. 499
 FIG. 500
 FIG. 501
 FIG. 502
 FIG. 503
 FIG. 504
 FIG. 505
 FIG. 506
 FIG. 507
 FIG. 508
 FIG. 509
 FIG. 510
 FIG. 511
 FIG. 512
 FIG. 513
 FIG. 514
 FIG. 515
 FIG. 516
 FIG. 517
 FIG. 518
 FIG. 519
 FIG. 520
 FIG. 521
 FIG. 522
 FIG. 523
 FIG. 524
 FIG. 525
 FIG. 526
 FIG. 527
 FIG. 528
 FIG. 529
 FIG. 530
 FIG. 531
 FIG. 532
 FIG. 533
 FIG. 534
 FIG. 535
 FIG. 536
 FIG. 537
 FIG. 538
 FIG. 539
 FIG. 540
 FIG. 541
 FIG. 542
 FIG. 543
 FIG. 544
 FIG. 545
 FIG. 546
 FIG. 547
 FIG. 548
 FIG. 549
 FIG. 550
 FIG. 551
 FIG. 552
 FIG. 553
 FIG. 554
 FIG. 555
 FIG. 556
 FIG. 557
 FIG. 558
 FIG. 559
 FIG. 560
 FIG. 561
 FIG. 562
 FIG. 563
 FIG. 564
 FIG. 565
 FIG. 566
 FIG. 567
 FIG. 568
 FIG. 569
 FIG. 570
 FIG. 571
 FIG. 572
 FIG. 573
 FIG. 574
 FIG. 575
 FIG. 576
 FIG. 577
 FIG. 578
 FIG. 579
 FIG. 580
 FIG. 581
 FIG. 582
 FIG. 583
 FIG. 584
 FIG. 585
 FIG. 586
 FIG. 587
 FIG. 588
 FIG. 589
 FIG. 590
 FIG. 591
 FIG. 592
 FIG. 593
 FIG. 594
 FIG. 595
 FIG. 596
 FIG. 597
 FIG. 598
 FIG. 599
 FIG. 600
 FIG. 601
 FIG. 602
 FIG. 603
 FIG. 604
 FIG. 605
 FIG. 606
 FIG. 607
 FIG. 608
 FIG. 609
 FIG. 610
 FIG. 611
 FIG. 612
 FIG. 613
 FIG. 614
 FIG. 615
 FIG. 616
 FIG. 617
 FIG. 618
 FIG. 619
 FIG. 620
 FIG. 621
 FIG. 622
 FIG. 623
 FIG. 624
 FIG. 625
 FIG. 626
 FIG. 627
 FIG. 628
 FIG. 629
 FIG. 630
 FIG. 631
 FIG. 632
 FIG. 633
 FIG. 634
 FIG. 635
 FIG. 636
 FIG. 637
 FIG. 638
 FIG. 639
 FIG. 640
 FIG. 641
 FIG. 642
 FIG. 643
 FIG. 644
 FIG. 645
 FIG. 646
 FIG. 647
 FIG. 648
 FIG. 649
 FIG. 650
 FIG. 651
 FIG. 652
 FIG. 653
 FIG. 654
 FIG. 655
 FIG. 656
 FIG. 657
 FIG. 658
 FIG. 659
 FIG. 660
 FIG. 661
 FIG. 662
 FIG. 663
 FIG. 664
 FIG. 665
 FIG. 666
 FIG. 667
 FIG. 668
 FIG. 669
 FIG. 670
 FIG. 671
 FIG. 672
 FIG. 673
 FIG. 674
 FIG. 675
 FIG. 676
 FIG. 677
 FIG. 678
 FIG. 679
 FIG. 680
 FIG. 681
 FIG. 682
 FIG. 683
 FIG. 684
 FIG. 685
 FIG. 686
 FIG. 687
 FIG. 688
 FIG. 689
 FIG. 690
 FIG. 691
 FIG. 692
 FIG. 693
 FIG. 694
 FIG. 695
 FIG. 696
 FIG. 697
 FIG. 698
 FIG. 699
 FIG. 700
 FIG. 701
 FIG. 702
 FIG. 703
 FIG. 704
 FIG. 705
 FIG. 706
 FIG. 707
 FIG. 708
 FIG. 709
 FIG. 710
 FIG. 711
 FIG. 712
 FIG. 713
 FIG. 714
 FIG. 715
 FIG. 716
 FIG. 717
 FIG. 718
 FIG. 719
 FIG. 720
 FIG. 721
 FIG. 722
 FIG. 723
 FIG. 724
 FIG. 725
 FIG. 726
 FIG. 727
 FIG. 728
 FIG. 729
 FIG. 730
 FIG. 731
 FIG. 732
 FIG. 733
 FIG. 734
 FIG. 735
 FIG. 736
 FIG. 737
 FIG. 738
 FIG. 739
 FIG. 740
 FIG. 741
 FIG. 742
 FIG. 743
 FIG. 744
 FIG. 745
 FIG. 746
 FIG. 747
 FIG. 748
 FIG. 749
 FIG. 750
 FIG. 751
 FIG. 752
 FIG. 753
 FIG. 754
 FIG. 755
 FIG. 756
 FIG. 757
 FIG. 758
 FIG. 759
 FIG. 760
 FIG. 761
 FIG. 762
 FIG. 763
 FIG. 764
 FIG. 765
 FIG. 766
 FIG. 767
 FIG. 768
 FIG. 769
 FIG. 770
 FIG. 771
 FIG. 772
 FIG. 773
 FIG. 774
 FIG. 775
 FIG. 776
 FIG. 777
 FIG. 778
 FIG. 779
 FIG. 780
 FIG. 781
 FIG. 782
 FIG. 783
 FIG. 784
 FIG. 785
 FIG. 786
 FIG. 787
 FIG. 788
 FIG. 789
 FIG. 790
 FIG. 791
 FIG. 792
 FIG. 793
 FIG. 794
 FIG. 795
 FIG. 796
 FIG. 797
 FIG. 798
 FIG. 799
 FIG. 800
 FIG. 801
 FIG. 802
 FIG. 803
 FIG. 804
 FIG. 805
 FIG. 806
 FIG. 807
 FIG. 808
 FIG. 809
 FIG. 810
 FIG. 811
 FIG. 812
 FIG. 813
 FIG. 814
 FIG. 815
 FIG. 816
 FIG. 817
 FIG. 818
 FIG. 819
 FIG. 820
 FIG. 821
 FIG. 822
 FIG. 823
 FIG. 824
 FIG. 825
 FIG. 826
 FIG. 827
 FIG. 828
 FIG. 829
 FIG. 830
 FIG. 831
 FIG. 832
 FIG. 833
 FIG. 834
 FIG. 835
 FIG. 836
 FIG. 837
 FIG. 838
 FIG. 839
 FIG. 840
 FIG. 841
 FIG. 842
 FIG. 843
 FIG. 844
 FIG. 845
 FIG. 846
 FIG. 847
 FIG. 848
 FIG. 849
 FIG. 850
 FIG. 851
 FIG. 852
 FIG. 853
 FIG. 854
 FIG. 855
 FIG. 856
 FIG. 857
 FIG. 858
 FIG. 859
 FIG. 860
 FIG. 861
 FIG. 862
 FIG. 863
 FIG. 864
 FIG. 865
 FIG. 866
 FIG. 867
 FIG. 868
 FIG. 869
 FIG. 870
 FIG. 871
 FIG. 872
 FIG. 873
 FIG. 874
 FIG. 875
 FIG. 876
 FIG. 877
 FIG. 878
 FIG. 879
 FIG. 880
 FIG. 881
 FIG. 882
 FIG. 883
 FIG. 884
 FIG. 885
 FIG. 886
 FIG. 887
 FIG. 888
 FIG. 889
 FIG. 890
 FIG. 891
 FIG. 892
 FIG. 893
 FIG. 894
 FIG. 895
 FIG. 896
 FIG. 897
 FIG. 898
 FIG. 899
 FIG. 900
 FIG. 901
 FIG. 902
 FIG. 903
 FIG. 904
 FIG. 905
 FIG. 906
 FIG. 907
 FIG. 908
 FIG. 909
 FIG. 910
 FIG. 911
 FIG. 912
 FIG. 913
 FIG. 914
 FIG. 915
 FIG. 916
 FIG. 917
 FIG. 918
 FIG. 919
 FIG. 920
 FIG. 921
 FIG. 922
 FIG. 923
 FIG. 924
 FIG. 925
 FIG. 926
 FIG. 927
 FIG. 928
 FIG. 929
 FIG. 930
 FIG. 931
 FIG. 932
 FIG. 933
 FIG. 934
 FIG. 935
 FIG. 936
 FIG. 937
 FIG. 938
 FIG. 939
 FIG. 940
 FIG. 941
 FIG. 942
 FIG. 943
 FIG. 944
 FIG. 945
 FIG. 946
 FIG. 947
 FIG. 948
 FIG. 949
 FIG. 950
 FIG. 951
 FIG. 952
 FIG. 953
 FIG. 954
 FIG. 955
 FIG. 956
 FIG. 957
 FIG. 958
 FIG. 959
 FIG. 960
 FIG. 961
 FIG. 962
 FIG. 963
 FIG. 964
 FIG. 965
 FIG. 966
 FIG. 967
 FIG. 968
 FIG. 969
 FIG. 970
 FIG. 971
 FIG. 972
 FIG. 973
 FIG. 974
 FIG. 975
 FIG. 976
 FIG. 977
 FIG. 978
 FIG. 979
 FIG. 980
 FIG. 981
 FIG. 982
 FIG. 983
 FIG. 984
 FIG. 985
 FIG. 986
 FIG. 987
 FIG. 988
 FIG. 989
 FIG. 990
 FIG. 991
 FIG. 992
 FIG. 993
 FIG. 994
 FIG. 995
 FIG. 996
 FIG. 997
 FIG. 998
 FIG. 999
 FIG. 1000